



USING BIM WITH THE LAST PLANNER SYSTEM TO IMPROVE CONSTRAINTS ANALYSIS

Bernardo M. Etges

Raquel H. Reck

Marcus T. Fireman

Jerusa L. Rodrigues

Eduardo L. Isatto



Introduction



- Last Planner System (LPS) has been **widely implemented** by construction companies who seek to **improve the reliability** of production at construction sites.
 - **Medium-term planning** as the **main element** that make up the LPS (Ballard, 1997; Ballard, 2000; Hamzeh, 2012; Pikas et al., 2012; Salvatierra et al., 2015; Al Hattab et al., 2017)
 - the main objective of which is to **protect the workflow** by **identify and remove constraints of activities**.
- Empirical studies have shown that **failures to do so** have led to jumps in **wastes emerging in day-to-day production** (Bortolazza; Formoso, 2006; Kemmer et al., 2007; Fireman et al., 2013; Leão et al., 2014; Ibarra et al., 2016, Hamzeh et al., 2012).
- Angelim et al. (2020) recently conducted a **systematic literature review** that identified that one of the major shortcomings when applying medium-term planning lies precisely in the **difficulty of identifying and removing constraints in advance**.



Introduction



- The **joint application of BIM** (Building Information Modeling) **with LPS** has been **strongly suggested as a way to assist** and streamline the **process of identifying and removing constraints** (Angelim et al., 2020; Fireman et al., 2013; Ibarra et al., 2016; Sacks et al., 2012).



BIM and LPS



- Toledo et al. (2016) compare two case studies **one using only LPS** and the **other using LPS and BIM**.
 - Even **without the use of BIM models in lookahead planning meetings**, the coordinated use of LPS and BIM generates:
 - **increase** in Percentage of Plan Completion
 - a **decrease** in reasons for non-compliance
 - a **shortening** of the meeting durations
 - and a **decrease** in the total number of design RFI

Data from **five case studies** from **three different companies** have been analyzed. The main objective is to **analyze how integrating BIM with the LPS system can enable constraints at the medium-term and work packages short-term.**



RESEARCH METHOD



- **Multiple exploratory case studies**
- The **criteria for selecting the five studies** were based on:
 - each one of them has a planning and control method based on the elements of Last Planner system;
 - has a history of implementing lean tools
 - provide access to information;
 - the companies are in the initial stage of implementing BIM.
- The work method consists of **two phases**:

Phase 1 - analyze which categories of **constraints** identified in medium-term planning could be modeled in BIM:

- a **database** was created
- categorized** according to its relation to: Material, Labor force, Equipment, Security, Project, and Planning
- focus group** regarding the possibility of modeling them

Phase 2 - examine the **percentage of work packages** elaborated in the short-term plan could be modeled in BIM:

- a **database** was created
- categorized** according to construction stage (masonry, infrastructure etc..).
- focus group** regarding the modeling them



RESEARCH METHOD



	Market	Case Study	Built area	Characteristics	Constructive Phase	Constraints	Analysis of work-packages
Company 1	Residential High-, Middle- and Low-income	Case 1	13.505,67 m ²	127 residential units 1 tower block - 2 stores	Infrastructure	22	91
		Case 2	80.902,05 m ²	576 residential units 4 tower blocks	All services	12	815
Company 2	Residential High-, Middle- and Low-income and Commercial	Case 3	10.150,67 m ²	Commercial+hotel 1 tower block with 168 private units	All services	-	297
		Case 4	32.405,82 m ²	Commercial+health 1 tower block with 423 private units	Finishings	51	-
Company 3	Metallic Construction System	Case 5	24.695 m ²	Expansion of Airport (Pier, Processor, Boarding bridges and Annexes)	Superstructure	132	39
Total						217	1242



Analysis of medium-term data



IGLC 28

BERKELEY, CA 6-12 JULY 2020

28th ANNUAL CONFERENCE OF THE
INTERNATIONAL GROUP FOR LEAN CONSTRUCTION

	Equipment	Material	Labor Force	Planning	Design	Safety
Residential 1	100% (3)	0% (0)	0% (0)	25% (1)	50% (1)	33% (1)
Residential 2	80% (4)	28% (10)	0% (0)	25% (14)	83% (10)	100% (3)
Commercial 2	0% (0)	0% (0)	0% (0)	29% (2)	50% (3)	
Industrial	100% (7)	100% (56)	0% (0)	43% (12)	100% (23)	



Analysis of medium-term data



IGLC 28

BERKELEY, CA 6-12 JULY 2020

28th ANNUAL CONFERENCE OF THE
INTERNATIONAL GROUP FOR LEAN CONSTRUCTION

	Equipment	Material	Labor Force	Planning	Design	Safety
Residential 1	100% (3)	0% (0)	0% (0)	25% (1)	50% (1)	33% (1)
Residential 2	80% (4)	28% (10)	0% (0)	25% (14)	83% (10)	100% (3)
Commercial 2	0% (0)	0% (0)	0% (0)	29% (2)	50% (3)	
Industrial	100% (7)	100% (56)	0% (0)	43% (12)	100% (23)	



Analysis of medium-term data



IGLC 28

BERKELEY, CA 6-12 JULY 2020

28th ANNUAL CONFERENCE OF THE
INTERNATIONAL GROUP FOR LEAN CONSTRUCTION

	Equipment	Material	Labor Force	Planning	Design	Safety
Residential 1	100% (3)	0% (0)	0% (0)	25% (1)	50% (1)	33% (1)
Residential 2	80% (4)	28% (10)	0% (0)	25% (14)	83% (10)	100% (3)
Commercial 2	0% (0)	0% (0)	0% (0)	29% (2)	50% (3)	
Industrial	100% (7)	100% (56)	0% (0)	43% (12)	100% (23)	



Analysis of medium-term data



IGLC 28


BERKELEY, CA 6-12 JULY 2020

28th ANNUAL CONFERENCE OF THE
INTERNATIONAL GROUP FOR LEAN CONSTRUCTION

	Equipment	Material	Labor Force	Planning	Design	Safety
Residential 1	100% (3)	0% (0)	0% (0)	25% (1)	50% (1)	33% (1)
Residential 2	80% (4)	28% (10)	0% (0)	25% (14)	83% (10)	100% (3)
Commercial 2	0% (0)	0% (0)	0% (0)	29% (2)	50% (3)	
Industrial	100% (7)	100% (56)	0% (0)	43% (12)	100% (23)	



ANALYSIS OF THE SHORT-TERM DATA



ANALYSIS OF THE SHORT-TERM DATA



- Analyzing the causes of the non-completion of activities as planned
 - All the causes of **Project** category can be modeled.
 - **Access** category can also be modeled as it represents the interference of the stages of the product, pieces of equipment, and workflows.
 - **Materials** category, only causes of lack of material due to losses above those expected could be modellable, since we would have more precise quantitative estimates of the materials.
 - **Equipment** category, a detailed study in the BIM model could avoid the causes of acquiring inappropriate equipment for the activity or bad dimensioning.
 - **Safety** category, delay in integration are not adjustable, but stoppages due to lack of collective protection.
- The **joint analysis** of medium-term **constraints and causes** of short-term non-completion **are convergent**, with a **high capacity for modeling** the categories of **project, equipment, access, and materials**.



CONCLUSIONS



- Analyzing **constraints** identified in medium-term planning and the **percentage of work packages** elaborated in short-term planning meetings that could be modeled in BIM:
 - We may conclude that **the integration of BIM with LPS** can **let constraints** in medium-term planning be identified and removed in a **more agile and efficient way**.
 - By **using the BIM 4D model** to support the modeling of constraints, it could be seen that the use of the BIM model throughout the PPC process **brings benefits** to the planning of the Construction project.
- Great **potential for modeling** medium-term **constraints and causes** of short-term in the BIM model was identified. This occurs mainly for those that refer to **Projects, Equipment, Work Safety, Materials**.



CONCLUSIONS



- The **use of BIM can be different in the planning horizons** defined by the LPS.
 - In the **medium term**, BIM can be used to **allow simulations and visualizations** of the position of teams, equipment, and sequence of activities to be simulated and visualized and to understand and visualize workflows.
 - in the **short term**, BIM enables **packages to be visualized in greater detail**, thus facilitating their correct definition, and can let different management systems come under integrated control.
 - We highlight the **use of BIM in planning meetings** both in the medium term (Construction Company 1) and in the short-term (Construction Companies 1 and 2) since the model **allows participants involved to have a common interpretation of the strategies** defined for the enterprise.
- As future studies, it is suggested the **common use of BIM model with LPS** by integrating the **modeling of the attributes and constraints** identified for a comparative case study that lets the potential gains be measured.





USING BIM WITH THE LAST PLANNER SYSTEM TO IMPROVE CONSTRAINTS ANALYSIS

Bernardo M. Etges

Raquel H. Reck

Marcus T. Fireman

Jerusa L. Rodrigues

Eduardo L. Isatto

