

Singularity Functions To Enhance Monitoring In The Last Planner System



Ali Ezzeddine, Masters Student, Department of Civil and Environmental Engineering, AUB, Lebanon, ame109@mail.aub.edu

Lynn Shehab, Masters Student, Department of Civil and Environmental Engineering, AUB, Lebanon, aas113@mail.aub.edu

Farook Hamzeh, Associate Professor, Civil and Environmental Engineering Dept., University of Alberta, Canada, hamzeh@ualberta.ca

Gunnar Lucko, Professor of Civil Engineering and Director, Construction Engineering and Management Program, Dept. of Civil Engineering, Catholic University of America, Washington, lucko@cua.edu



Presentation Outline

Research Gap / Goal

Last Planner System

Control in Planning


Singularity Functions


Methodology

Developed Tool

Simulation

Conclusion






Research Gap



Goal





Last Planner System

Master Scheduling



Planners identify project milestones and major activities and perform push scheduling using the critical path method (CPM) to estimate the total project's duration (Hanzeh et al. 2008)

SHOULD

Phase Scheduling



Planner break down phases developed in the master schedule into activities, identify gross constraints, and perform reverse phase scheduling (Hamzeh 2009)

CAN

Lookahead Planning



Planners break down tasks from the phase schedule, design and detail their execution, and remove constraints to make tasks ready (Junnonen and Seppänen 2004)

WILL



Weekly Work Plan (WWP)



Planners should include sound assignments that are made ready by removing any constraints that prevent them from becoming ready for execution. (Ballard 2000)

DID

LPS Metrics Used





Control in LPS & Linear Scheduling

SHOULD & CAN

SHOULD and CAN rather than just SHOULD and DID (Howell and Ballard 1996)



Monitor

Actual Progress



Production Unit & Workflow

Ensure better workers assignments & ensure the best work sequence (Ballard 2000)



Forecast

Future Progress



Early Constraints Identification and Removal

To facilitate work plans' reliability (Hamzeh 2009)



Alert

Cascading Delays and Clashes (Seppänen 2013)



Metrics


For continuous improvement and learning from failures



Buffer


Time - Space - Plan (Frandsen 2015)





Singularity

Functions



Macaulay (1919)



Föppl (1927)



S = strength

x = variable under consideration

a = activation point

n = behavior shape


If n = 0 → step

If n = 1 → slope



$$S < x - a >^n = \begin{cases} 0 & \text{for } x < a \\ (x - a)^n & \text{for } x \geq a \end{cases}$$

Singularity Functions in Construction Management



Singularity Functions Example


$$W(t) =$$


$$+ 1 \langle t - 0 \rangle^1$$

$$+ 2 \langle t - 2 \rangle^1$$


$$- 8 \langle t - 4 \rangle^0$$


$$- 3 \langle t - 4 \rangle^1$$





Methodology





Overview

Item



Forecast Activity Data

Actual Activity Data

Improvement of Activity

Resources Data

Input



Start Time
End Time
Work to be done

Actual Start Time
End Time Before Improvement
Work Done So Far

Required End Time

Number of Workers
Maximum Production Rate
Working Area
Congestion Limit

Output




Planned Production Rate

Actual Production Rate
PRI
Warning of Cascading Delays
Prediction of Metrics

Required Improved Production Rate

Modified Maximum Production Rate
Warning of Resource Allocation if needed
Warning of Congestion

Visual Monitoring





Proposed Metric

Percent Improvement Complete

PIC

$$\text{PIC} = \frac{\text{No. of Activities That Needed Improvement and Were Completed}}{\text{No. of All Activities That Needed Improvement}}$$

$$\text{PIC} = \frac{\text{Should \& Did Improve}}{\text{Should Improve}}$$


Purpose

Shows the reliability, ability, and commitment of the team in finishing the tasks that needed improvement




Example


• Activity A Wf • Activity A Wn • Activity A Wi



• Activity B Wf • Activity B Wn • Activity B Wi



• Activity C Wf • Activity C Wn • Activity C Wi



of Tasks that need Improvement


3

of Tasks that need Improvement +
were completed

2

Percent Improvement Complete (PIC)

67%




THE NEED FOR SIMULATION




Lack of an ABM & DES
Simulation Model



Metrics Not Used In Production
Rate Calculation



Simulation



DES



ABM



- **Dynamic**
- **Stochastic**
- **Process-centric**
(chain of activities and resources linked together)

- **Agents and their interactions**
- **High complexities and interdependencies**
- **3 aspects**
 - Identify agents (attributes)
 - Agent relationships
 - Agent environment

Overview

Purpose: Achieve more accurate values of the Improved Production Rate (IPR) obtained from singularity functions

Inputs from
EXCEL

- Congestion
- Time remaining for improvement
- Minimum, mode and maximum values for PIC, PRI, PPC and CLR

Input
Analysis

- DES
- ABM

Output

- Modified Time left for improvement and converted into a graphical production rate form in EXCEL
- Find the “most likely” production rate




Figure 1 - Discrete-Event Process




Figure 2 - User Dashboard




Figure 3 - Crew Statechart

Run the model



Calculate modified duration 1000 times



Convert each modified duration into a production rate



The "most likely" IPR is automatically calculated



Realistic approximation of the rate that the crew will most probably work at to execute the work required, by taking into account congestion, idleness, and the LPS metrics





Figure 4 - Anylogic Flowchart

Simulation Runs


Time left for improvement = 1 day

Experiment	Min. Metrics	Mode Metrics	Max. Metrics	Congestion	Mean Duration	Most Likely IPR
Good performance	0.7	0.9	1	0.2	1.65	6.84
Average performance	0.4	0.6	0.8	0.5	3.38	4.18
Bad performance	0.1	0.4	0.5	0.9	7.41	2.54

Production Rates



■ Production Rates ● Mean



Conclusion & Future Research

- A tool to monitor project performance at the level of the WWP of LPS
- Singularity functions to monitor and forecast activity progress
- Several metrics from the LPS are used
- A new metric (PIC) is suggested for the reliability to implement required improvements during execution.
 - Shows the reliability of the promises made during the week of execution
 - Use along with the maximum production rates that are modified by PRI to ensure that the required improvements are rational and within the crew's capacity.



- Additional metrics can be developed showing the volume of improvement
- This method should be tested on an actual project as a case study and refinements could be made.
- Improvements in the production rates should be linked to Takt Time for all the activities.



Thank You